

D2 SERIES HEAVY DUTY DEADBOLT



2" ADA Approved Thumb Turn with
3/32" Steel Mounting plate



Specification

ANSI: Meets & Exceeds ANSI - A 156.2, Grade 2 Standards

UL Listings: UL Listed for "A" Label 3 Hour Fire Doors

ADA Compliance: 2" ADA Thumbturn Meets ADA & ANSI A117. 1 accessibility codes

Lock Chassis: Steel, Zinc dichromated for corrosion resistance

Trim: Free spinning cylinder collar resists wrenching and prying

Handing: Non-handed - Completely reversible

Backset & Latchface : 2 3/4" fixed backset std. with 1 1/8" x 2 1/4" latchface, 2 3/8" backset available with 1" x 2 1/4" latchface both with self adjusting front for square or beveled doors

Latchbolt: Grade 1 Solid Brass with 1" Throw & Anti-Saw Hardened Steel Pin Insert

Cylinder Options: 6 Pin Brass, C Kwy, with 2 Keys std, Prepared for Small format IC core (less core)

Strike: 1 1/8" x 2 3/4" Square corner

Door Preparation : ANSI A115.2 - 2 1/8" crossbore

Door Thickness: 1 3/4" thick doors

Standard Finishes : US3 PVD*, US4, US10B, US15, US26 PVD*, US26D (PVD = Lifetime Finish)

Fasteners: Combination screws for wood or metal doors & frames

Warranty: Limited lifetime warranty