

# 1000 SERIES HEAVY DUTY SVR EXIT DEVICE



## Specification

- ANSI:** Meets ANSI A156.3 - Grade 1 Standards
- UL Listings:** Panic Exit, 3 Hr Fire Doors to 8'-0" x 10'-0" & LBR up to 8'-0" x 8'-0"
- ADA:** Meets ADA requirements ANSI A117.1 with Lever Trim
- Handing:** Easily Re-handed in the field - Shipped as RHR
- Construction:** Heavy Duty Extruded Anodized Aluminum Channel & Steel Chassis
- Finishes:** US3, US4, US10B/US19, US26, US32D on Headcover, Pushbar, Endcap & Latches
- Marine Grade:** Marine Grade 316 Stainless Steel option available
- Top Latch:** U Shaped Top Latch for Secure Engagement with strike (not electric strike compatible)
- Bottom Latch:** Drop Bolt Style Bottom Latch Secures into flat strike & hole in the floor
- Dogging:** 5/32" Hex Key Dogging Standard on Panic Exit Hardware
- Cylinder Dogging:** Cylinder Dogging Kits available for new or existing exit devices
- Device Lengths:** 33" for 3'-0" wide doors and 42" for 3'-8" to 4'-0" wide doors
- Min. Door Width:** 33" device can be cut down to fit on 2'-8" wide door  
42" device can be cut down to fit on 3'-4" wide door
- Door Heights:** 7"-0" Standard - Extended Top Rods available for up to 10'-0" tall doors
- Center Case Dim:** 8" Height x 2 7/8" Wide x 2 13/16" Thick - 4 1/2" Minimum stile required
- Mechanism Case Dim:** 2 3/16" Height x 2 3/16" Wide
- Projection:** 3 3/8" Undogged - Pushbar Neutral & 2 13/16" Dogged - Pushbar Depressed
- Fasteners:** Wood, Machine & Self Tapping Machine Screws (F1000V includes thru bolts)
- Trim & Accessories:** Latch filler included, Exterior Trims, Shim Kits & other accessories available
- Electrified Options:** ELR - Motorized Electric latch retraction, REX - Request to exit,
- Under Cut:** 1/4" door under cut recommended for 1/4" threshold or no threshold openings
- Warranty:** Limited Lifetime Warranty