

# 1000 SERIES HEAVY DUTY RIM EXIT DEVICE



US4



## Specification

- ANSI:** Meets ANSI - A156.3 - Grade 1 Standards
- UL Listings:** UL Listed for Panic Exit Hardware
- (Optional) Fire Rating:** UL Listed for "A" Label 3 Hour Fire Doors (no dogging on rated devices)
- ADA:** Meets ADA requirements ANSI A117.1 with Lever Trim
- Handing:** Non Handed • Completely Reversible
- Construction:** Heavy Duty Extruded Anodized Aluminum Channel & Steel Chassis
- Finishes:** US3, US4, US10B/US19, US26 & US32D on Headcover, Pushbar & End Cap
- Marine Grade:** Marine Grade 316 Stainless Steel option available
- Latchbolt:** Deadlocking latchbolt with 5/8" projection
- Strike:** Roller Strike with 5/8" projection & 1/8" shim
- Dogging:** 5/32" Hex Key Dogging Standard on Panic Exit Hardware only
- Cylinder Dogging:** Cylinder Dogging Kits available for new or existing exit devices
- Device Lengths:** 33" for 3'-0" wide doors and 42" for 3'-8" to 4'-0" wide doors
- Min. Door Width:** 33" device can be cut down to fit on 2'-8" wide door  
42" device can be cut down to fit on 3'-4" wide door
- Center Case Dim.:** 8" Height x 2 7/8" Wide x 2 13/16" Thick - 4 1/2" Minimum stile required
- Mechanism Case Dim.:** 2 3/16" Height x 2 3/16" Wide
- Projection:** 3 3/8" Undogged • Pushbar Neutral & 2 13/16" Dogged • Pushbar Depressed
- Fasteners:** Wood, Machine & Self Tapping Machine Screws (F1000R includes thru bolts)
- Trim & Accessories:** ASA & latch fillers included, Exterior Trims, Shim Kits & other accessories available
- Alarmed Exits:** Exit Alarm Kit ALK-1000 available for new or existing devices
- Electrification:** ELR • Motorized Electric latch retraction, REX • Request to exit
- Warranty:** Limited Lifetime Warranty

