316R SERIES REPLACEMENT DOOR CLOSER



Specification



| of their respective companies and are not affiliated with Design | Sargent: 1430 | | | |
|---|---|---------------------------|---------|--------------------|
| model numbers may or may not be copyright or registered trademarks | Ryobi/Stanley: 1650, 3500, 4500 | | | |
| Note: The noted company names & | Norton: 1600, 8100, 8300, 8500, 7500, 7700 | | | , |
| | LCN: 4041, 4110, 1460 | BZ/BLK | 690/693 | BZ/Black Painted |
| | Dor-O-Matic: SC60, SC70, SC80 | AL | 689 | Aluminum Painted |
| | Dorma: 8600, 7200, 7300 | DH# | BHMA# | Finish Description |
| | Design Hardware: 116, 316, 416 | Available Finishes | | |
| Replaces: | Corbin Russwin: 3200, 3600, 6200, 6400 | | | |
| Warranty: | Limited lifetime warranty | | | |
| Fasteners: | Thru bolts with machine screws, wood screws & self tapping machine screws | | | |
| Projection: | Slim 2 1/4" projection with cover installed over mtg. plate | | | |
| CTC Hole Pattern: | 2 holes 1" CTC, 3" CTC horizontal x 2 1/4" CTC vertical | | | |
| Cover: | Molded Plastic Cover included to conceal mounting plate | | | |
| Valves: | Staked Valves to prevent backing valves out too far | | | |
| Back Check: | Back Check Intensity Control Standard | | | |
| Speed Controls: | Independent Latch & Sweep Speed Controls | | | |
| Spring Sizing: | Adjustable Spring Power from size 1 to 6 - Factory set at size 3 | | | |
| Closer Body: | Heavy Duty Cast Aluminum Closer Body, Rack & Pinion Const. | | | |
| ADA Compliance: | Meets ADA requirements ANSI A117.1 | | | |
| UL Listings: | For "A" Label 3 Hour Fire Doors, UL10C Positive Pressure Rated | | | |
| ANSI: | Meets ANSI A156.4 Grade 1 Standards | | | |
| Mounting Plate: | Includes Patented Mounting Plate - Patent# 7698796 Mounting Plate can be used to replace a wide variety of the most popular door closers on the market without drilling new holes in the door | | | |