

416 SERIES HEAVY DUTY DOOR CLOSER



Specification

- ANSI:** Meets ANSI A156.4 Grade 1 Standards
- UL Listings:** For "A" Label 3 Hour Fire Doors, UL 10C Positive Pressure Rated
- ADA Compliance:** Meets ADA requirements ANSI A117.1
- Closer Body:** Heavy Duty Cast Iron Closer Body with Precision Rack & Pinion Construction
- Piston & Spindle:** Heat Treated Steel Piston & Spindle with Needle Bearings for Smooth Operation
- Springs:** Heat Treated Heavy Duty Tempered Spring for up to 250 lb door
- Spring Sizing:** Adjustable size 1 to 6 - Factory set at size 3
- Speed Controls:** Independent Latch & Sweep Speed Controls
- Back Check:** Adjustable Back Check Intensity Control Valve
- Valves:** Staked Valves to prevent backing valves out too far
- Standard Cover:** Molded Plastic Cover included for finished look
- CTC Hole Pattern:** 2 holes 1" CTC, 3" CTC horizontal x 2 1/4" CTC vertical
- Projection:** 2 1/4" projection with cover installed
- Minimum Top Rail:** Regular: 3 3/4" - Top Jamb: 1 1/4" - Parallel Arm: 5 3/8"
- Fasteners:** Thru bolts & machine screws, wood screws & self tapping machine screws included
- Mounting Styles:** Includes all screws and brackets for Regular, Top Jamb and Parallel Arm Installations
- Accessories:** Hold Open Arms, Heavy Duty Arms, Drop Plates, Extended Arms & more...
- Warranty:** Limited lifetime warranty