

D1 SERIES EXTRA HEAVY DUTY DEADBOLT



2" ADA Approved Thumbturn with
1/8" Steel Mounting Plate



Specification

ANSI: Meets ANSI - A156.2, Grade 1 Standards

UL Listings: UL Listed for "A" Label 3 Hour Fire Doors

ADA Compliance: 2" ADA Thumbturn Meets ADA & ANSI A117.1 accessibility codes

Lock Chassis: Steel, Zinc dichromated for Corrosion Resistance
Steel Security Shield included to protect bolt from ice pick attack through door

Trim: Free spinning Solid Steel cylinder collar resists wrenching and prying

Handing: Non-Handed - Completely reversible

Backset & Latchface : 2 3/4" fixed backset std. with 1 1/8" x 2 1/4" latchface, 2 3/8" backset available with 1" x 2 1/4" latchface both with self adjusting front for square or beveled doors

Latchbolt: Solid Brass with 1" Throw & Anti-Saw Hardened Steel Pin Insert

Cylinder Options: 6 Pin Brass, C Kwy, with 2 Keys std, Prepared for Small format IC core (less core)

Strike: 1 1/8" x 2 3/4" Square corner, Wood Frame Reinforcer & 3" screws also included

Door Preparation : ANSI A115.2 - 2 1/8" crossbore on doors

Door Thickness: 1 3/4" thick doors

Standard Finishes : US3 PVD*, US10B, US15, US26 PVD*, US26D (PVD= Lifetime Finish)

Fasteners: Combination screws for wood or metal doors & frames

Warranty: Limited Lifetime Warranty