

J SERIES HEAVY DUTY GRADE 2 LEVER LOCK



(Thru Bolted)



Specification

- ANSI:** Meets ANSI - A156.2, Grade 2 Standards
- UL Listings:** UL Listed for "A" Label 3 Hour Fire Doors
- ADA Compliance:** Meets ADA and ANSI A117.1 accessibility codes
- Lock Chassis:** Steel, Zinc dichromated for Corrosion Resistance
- Trim:** 5" Solid zinc diecast levers, 3 3/8" wrought brass roses
- Lever Return:** Anti-sag mechanism with independent lever return springs to prevent lever sag
- Handing:** Non-Handed - Completely reversible (S-A & S-B lever styles are handed)
- Backset & Latchface:** 2 3/4" backset std. with 1 1/8" x 2 1/4" latchface, 2 3/8" backset is available with 1" x 2 1/4" latchface both with self adjusting front for square or beveled edge doors
- Latchbolt:** Stainless Steel with 1/2" projection, Deadlocking on keyed functions & exit latch
- Cylinder Options:** 6 Pin Brass, C Kwy, with 2 Keys or Prepared for Small format IC core (less core)
- Strikes:** 4 7/8" x 1 1/4" ASA standard -T strike & Full lip strikes available
- Door Preparation:** ANSI A115.2 - 2 1/8" crossbore with (2) 3/8" Thru bolt holes
- Optional Thru Bolts:** Removable Thru Bolts - Can be installed without thru bolts
- Door Thickness:** Factory Set for 1 3/4" - can be adjusted to fit 1 3/8" up to 2" thick
- Standard Lever Design:** Flat (standard - stocked in US26D, US10B, US19)
- Other Lever Choices:** Curved, Half Curved, S-A & S-B
- Standard Finish:** US26D, US10B, US19 (in stock in flat lever)
- Special Order Finishes:** US3 PVD*, US4, US15, US19, US26 PVD* (PVD = Lifetime Finish)
- Fasteners:** Combination screws for wood or metal doors & frames
- Warranty:** Limited Lifetime Warranty