

D1 SERIES FUNCTIONS & OPTIONS



Standard Cylinder



- D1-S Single Cylinder
- D1-D Double Cylinder
- D1-S-CL Single Cyl. Classroom
- D1-S-BP Single Cyl. x Blank Plate


Prepared for IC Core



- D1-S-IC Single Cylinder
- D1-D-IC Double Cylinder
- D1-S-IC-CL Single Cyl. Classroom
- D1-S-IC-BP Single Cyl. x Blank Plate

Outside/ Inside	Series/ Function	Type	ANSI No.	Function Description
	D1-S D1-S-IC	Single Cyl.	E21511	Deadbolt thrown or retracted by key from outside or by inside thumbturn. Bolt automatically deadlocks when thrown.
	D1-D D1-D-IC	Double Cyl.	E21411	Deadbolt thrown or retracted by key from either side. Bolt automatically deadlocks when fully thrown.
	D1-S-CL D1-S-IC-CL	Single Cyl. Classroom	E01711	Deadbolt thrown or retracted by key from outside. Inside thumbturn will retract bolt only and cannot throw bolt. Bolt automatically deadlocks when fully thrown.
	D1-S-BP D1-S-IC-BP	Single Cyl. x Blank Plate	E01611	Deadbolt thrown or retracted by key only. Blank plate inside. Bolt automatically deadlocks when fully thrown.

Stock Finishes



US3*	Bright/Polished Brass *PVD
US4	Brushed/Satin Brass
US10B	Oil Rubbed Bronze
US26*	Bright/Polished Chrome *PVD
US26D	Brushed/Satin Chrome
US15	Brushed/Satin Nickel

*PVD Lifetime Finish Standard on US3 and US26 finishes
PVD = Physical Vapor Deposition

How to Order

Series Function Finish
D1 - S-SFIC - US26D

Function Codes

S = Single Cylinder
D = Double Cylinder
SFIC = Prepared for Small Format IC
SLFIC = Prepared for Schlage Large Format IC
CL = Classroom Function
BP = Blank Plate
T = Thumbturn