M SERIES EXTRA HEAVY DUTY GRADE 1 LOCK



Small Format IC 6 or 7 pin





Specification

| ANSI: | Meets ANSI - A156.13, Series 1000, Grade 1 Standards | | |
|-----------------------|--|---|--|
| UL Listings: | UL Listed for "A" Label 3 Hour Fire Doors, Singles or Pairs | | |
| ADA Compliance: | Meets ADA and ANSI A117.1 accessibility codes with lever trim | | |
| Lock Case: | 2 3/4" Backset with Heavy Gauge Zinc Dichromated Steel | | |
| Levers: | 5" Full Length cast Zinc | | |
| Trim: | 2 1/4" x 8 1/8" Cast Escutcheon or 3" Wrought Brass Roses | | |
| Lever Return: | Independent lever return springs to prevent lever sag | | |
| Trim Attachment: | Thru bolted Lever for increased security | | |
| Handing: | Handed as RHR - Easily Rehanded in the field | | |
| Armored Front: | Wrought Stainless Steel or Brass 11/4" x 8" | | |
| Latchbolt: | Stainless Steel 3 Piece Anti Friction with 3/4" projection | | |
| Deadlocking: | Non handed Stainless Steel Deadlatch M• 19 | M• 19 x FS x US260 Privacy Indicator | |
| Deadbolt: | 1" Throw, Stainless Steel with a Anti-Saw Pins Priv | | |
| Cylinders & Cam: | C Keyway 6 pin -1 1/4" for Sectional & 1 3/8" for Escutcheon with DH M series cam Prepared for Small format IC core (less core) | | |
| Strikes: | 4 7/8" \times 1 1/4" ASA non handed with large rectangular cut out | | |
| Stock Trim & Lever: | Flat Sectional & Flat Escutcheon | | |
| Special Order Levers: | | | |
| Finishes: | | | |
| Electrified Options: | Motor Driven lock/unlock function 12/24 V (AC/DC) Fail Safe/Fail Secure Rex- Request to Exit | | |
| Warranty: | Limited lifetime warranty | M-32-IND Escutcheo | |

design hardware"

