

Z SERIES EXTRA HEAVY DUTY GRADE 1 LOCK



Small Format IC 6 or 7 pin



Specification

- ANSI:** Meets ANSI - A156.2, Series 4000, Grade 1 Standards
- UL Listings:** UL Listed for "A" Label 3 Hour Fire Doors
- ADA Compliance:** Meets ADA and ANSI A117. 1 accessibility codes
- Cycle Testing:** Tested to over 2 Million Cycles
- Lock Chassis:** Steel, Zinc dichromated for corrosion resistance
- Clutching:** Clutching levers standard for vandal resistance on locking functions
- Trim:** 5" Solid zinc diecast levers, 3 1/2" wrought brass roses
- Lever Return:** Independent lever return springs to prevent lever sag
- Handing:** Non-handed - Completely reversible
- Standard Latch:** 2 3/4" backset with 1 1/8" x 2 1/4" latchface - Stainless steel latch bolt with 3/4" projection
- Optional Latches:** 2 3/4" backset with 1 1/8" x 2 1/4" latchface - Stainless steel latch w/ 1/2" projection
2 3/8" backset with 1" x 2 1/4" latchface - Stainless steel latch w/ 1/2" projection
- Cylinder Options:** 6 Pin Brass, C Kwy, with 2 Keys std, Prepared for Small format IC core (less core)
Prepared for Schlage Large Format IC core (less core)
- Strikes:** 4 7/8" x 1 1/4" ASA standard - T strike & Full lip strikes available when specified
- Door Preparation:** ANSI A115.2 - 2 1/8" crossbore with (2) 5/16" thru bolt holes
- Door Thickness:** Factory Set for 1 3/4" - can be adjusted to fit 1 3/8" to 2" thick doors
- Lever Designs:** Flat (standard, shown above), Curved & Half Curved
- Standard Finishes:** US26D (In stock)
- Special Order Finishes:** US3 PVD*, US4, US10B, US26 PVD* (PVD = Lifetime Finish) (2 week lead time)
- Lead Lining Option:** 1/32" lead lined rose & 1/32" lead wrapped latch bolt (requires 1" bore)
- Electrified Options:** Motor Driven lock/unlock function, 12/24 V (AC/DC) Fail Safe/Fail Secure
REX - Request to Exit Switch, See electrified section
- Warranty:** Limited lifetime warranty