

V SERIES STANDARD DUTY GRADE 2 LEVER LOCK



(Non Thru Bolted)



Specification

- ANSI:** Meets ANSI - A156.2, Series 4000, Grade 2 Standards
- UL Listings:** UL Listed for "A" Label 3 Hour Fire Doors
- ADA Compliance:** Meets ADA and ANSI A117.1 accessibility codes
- Lock Chassis:** Steel, Zinc dichromated for Corrosion Resistance
- Clutching** Clutching levers standard for Vandal Resistance on locking functions
- Trim:** 5" Solid zinc diecast levers, 3" wrought brass roses (will not cover thru bolt holes)
- Lever Return:** Anti-sag mechanism with independent lever return springs to prevent lever sag
- Handing:** Non-Handed - Completely reversible (S-A & S-B lever styles are handed)
- Backset & Latchface:** 2 3/4" backset std. with 1 1/8" x 2 1/4" latchface, 2 3/8" backset is available with 1" x 2 1/4" latchface both with self adjusting front for square or beveled edge doors
- Latchbolt:** Stainless Steel with 1/2" projection, Deadlocking on keyed functions
- Cylinder Options:** 6 Pin Brass, C Kwy, 2 keys std or Prepared for Small format IC (less core)
- Strikes:** 4 7/8" x 1 1/4" ASA (standard) - 2 3/4" T strike & Full lip strike w/ 1/4" R.C available
- Door Preparation:** ANSI A115.2 - 2 1/8" crossbore
- Standard Lever Design:** Flat, Curved & Half Curved
- Other Lever Choices:** S-A & S-B levers available (2 week lead time)
- Standard Finishes:** US26D & US10B (in stock in Flat lever) - US26D (in stock in Curved & Half curved lever)
- Special Order Finishes:** US3 PVD*, US4, US15, US26 PVD* (PVD = Lifetime Finish) (2 week lead time)
- Fasteners:** Combination screws for wood or metal doors & frames
- Warranty:** Limited Lifetime Warranty