LE TRIM HEAVY DUTY LEVER ESCUTCHEON TRIM







LE-02DT Dummy





Specification

ANSI: ANSI A156.3, Grade 1

ADA: Meets ADA requirements ANSI A117.1

Construction Steel, Zinc Dichromated Chassis - Stainless Steel Exterior Housing

Application: Heavy Duty trim option for use with all 1000 & 2000 series exit devices

Mounting: Thru bolted design thru bolts to head of exit device

Spindle: 5/16" Square, Steel - Machined & Heat Treated

Lever: 5" Solid Stainless Steel lever - 27/8" total projection

Lever Designs: Flat (standard, shown above) & Curved

Escutcheon: 3" Wide x 9" Height x 3/4" Projection -Will cover 161 door prep

Handing: Non-Handed, Field selected at the time of installation

Door Thickness: 13/4" standard-Thick door kits available for 2" thick doors

Functions: O2DT Dummy, O8 Entry (convertible to O3NL - Night latch), O8A Passage

Fasteners: Includes thru bolt posts and 1/4"-20 machine screws for installation

Standard Cylinder: 11/8" Mortise cylinder with std. cam (included) - 6 Pin Brass, C Kwy, with 2 Keys

Optional Cylinders: 13/8" Mortise cylinder housing for 6 or 7 pin Small format IC core (less core)

Finishes: US3, US4, US10B/US19, US26, US32D (Type 304SS standard)

(Marine Grade 316SS option)

Accessories: 1/8" Cylinder collar spacer rings - (2 are supplied with IC housings)

Electrified Options: 12/24 Volt AC/DC - Fail Safe/Fail Secure Field selectable

Warranty: Limited lifetime warranty



